



Pressure Switches

Model:D500/8D

The Sensor of Switch is Diaphragm type, it can be suitable for air, gas such neutral gas and water, hydraulic oil, light fuel, lube and other fluid medium which would not exert corrosion to pressure sensor material. The Set Point of the Switch is adjustable, the adjustable range is from 0.02 MPa to 3Mpa



上海远仪控制器厂有限公司


Tel: (021)56325599 56983311 69927271

Fax:69927273 <http://www.shyuanyi.com>

□Main Technical Performance

Working viscosity: $<1 \times 10^{-3} \text{m}^2/\text{s}$
 Switching element: Micro-switches
 Protection Class: IP65
 Ambient temperature: $-5 \sim 40^\circ\text{C}$
 Fluid temperature: $0 \sim 90^\circ\text{C}$
 Vibrations: Max: 100m/s^2
 Repeatability: $\leq 1.5\%$
 Electrical rating: AC 220V 6A

Switching Function: Microswitch SPDT



Terminals 1-3:

Contacts close on rising pressure

Terminals 1-2:

Contacts open on rising pressure

□Features

Mini Structure, good Anti-vibration

□Characteristic date

Adjustable Range MPa	Switching pressure difference		Max. Allowable Pressure ¹⁾ MPa	Number of switching cycles Z(1/min)	Pressure sensor materials		Connection Type ²⁾	Connection (Internal thread)	Weight (kg)	Drawing No.	Cat. No.	
	Lower range MPa	Upper range MPa			Housing	Diaphragm /Seal						
Switching pressure difference not adjustable / Setscrew protected by plastic cover												
0.02...1.2	0.09	0.14	5	60	AL	NBR	I	G1/4"	0.4	01	0820150	
0.05...3	0.1	0.2	5	60			I	G1/4"	0.4	01		0820750
0.02...1.2	0.09	0.14	5	60			P	-	-	0.4	02	0820250 0820850
0.05...3	0.1	0.2	5	60			P	-	-	0.4	02	
Switching pressure difference not adjustable / With scaled rotary button												
0.02...1.2	0.09	0.14	5	60	AL	NBR	I	G1/4"	0.45	03	0820160	
0.05...3	0.1	0.2	5	60			I	G1/4"	0.45	03	0820760	

Notes: ¹⁾ Even shot pressure peaks must not exceed this value (=max. test pressure)

²⁾ I-Internal thread P-Flange



□ Dimensional drawing	□ Accessories
<p>01</p>	<p>Reducer G1/2 to G1/4 external thread Cat. No. 0574767</p>
<p>02</p>	<p>Surge damper G1/4 Cat. No. 0574773</p>
<p>03</p>	<p>Three-way-connection Screw-off the bolt, pressure gauge with $\Phi 60$ can be directly connected Cat. No. SC5 470 505</p>



Switch selection and mounting instructions

The switching points should normally be in about the middle of the adjustable range. Observe switching pressure during normal operation. Do not exceed electrical ratings. Electrical connection by a M18x1.5 cable gland, in accordance with local regulations. For outdoor installation sufficient protection has to be provided for Critical conditions are: Aggressiveness of air, high or low temperatures, drastic changes in temperature, solar radiation, penetration of water. For liquid media with pressure peaks and /or pulsating pressure, install surge damper upstream to eliminate scattering of switching points and excessive wear.

Setting of switching points

Versions with adjustment by screw with hex.
Recessed hole :

Loosen check nut, then set lower switching point.
The upper switching point is determined by the fixed switching pressure difference.

Versions with adjustment by scaled rotary button:
Loosen slot bolt, then set lower switching point.
The upper switching point is determined by the fixed switching pressure difference.

Turning the setting device clockwise shifts switching points upwards.

Use pressure gauge for precise setting (a pressure switch – even if provided with a scale – is not a measuring instrument). Switches can be adjusted even during operation. Depending on the design, setting can be arrested by either check nut or slot bolt.

